

What Is Claimed Is:

1. An image sensing apparatus comprising:
an operation unit to set image sensing conditions;
5 memory to store the image sensing conditions;
determination means for determining whether or not
a predetermined image sensing condition was set when the
image sensing apparatus was last shut down; and
control means for, in a case where the
10 predetermined image sensing condition was set,
controlling to read the image sensing conditions stored
in said memory and set the image sensing conditions in
the image sensing apparatus when turning on the image
sensing apparatus.

15

2. The image sensing apparatus according to claim
1, wherein in a case where said determination means
determines that the predetermined image sensing
condition was not set, said control means controls to
20 set default image sensing conditions in the image
sensing apparatus when turning on the image sensing
apparatus.

3. The image sensing apparatus according to claim
25 1, wherein said predetermined image sensing condition is
a manual image sensing mode.

4. The image sensing apparatus according to claim 1, wherein said predetermined image sensing condition is an ON state of storing image sensing conditions.

5 5. The image sensing apparatus according to claim 1, wherein said determination means also determines whether or not a predetermined image sensing condition is set, and the image sensing conditions are stored in a case where the predetermined image sensing condition is
10 set.

6. The image sensing apparatus according to claim 5, wherein said predetermined image sensing condition is a manual image sensing mode.
15

7. The image sensing apparatus according to claim 5, wherein said predetermined image sensing condition is an ON state of storing image sensing conditions.

20 8. The image sensing apparatus according to claim 1, wherein the image sensing conditions are stored at a time of shutting down the image sensing apparatus.

9. The image sensing apparatus according to claim 25 1, wherein the image sensing conditions are stored at a time designated by a user.

10. The image sensing apparatus according to claim 1, wherein all of the image sensing conditions are stored in said memory.

5 11. The image sensing apparatus according to claim 1, wherein at least one of the image sensing conditions is stored in said memory.

10 12. A control method for an image sensing apparatus comprising:

a determination step of determining whether or not a predetermined image sensing condition was set when the image sensing apparatus was last shut down;

15 a reading step of, in a case where the predetermined image sensing condition was set, reading the image sensing conditions stored in memory; and

a setting step of setting the read image sensing conditions in a case where the predetermined image sensing condition was set, or default image sensing conditions in a case where the predetermined image sensing condition was not set, in the image sensing apparatus when turning on the image sensing apparatus.

25 13. The control method according to claim 12, wherein said predetermined image sensing condition is a manual image sensing mode.

14. The control method according to claim 12,
wherein said predetermined image sensing condition is an
ON state of storing image sensing conditions in the
memory.

5

15. The control method according to claim 12
further comprising:

a step of determining whether or not a
predetermined image sensing condition is set; and

10 a storage step of storing the image sensing
conditions in a case where the predetermined image
sensing condition is set.

16. The control method according to claim 15,
15 wherein said predetermined image sensing condition is a
manual image sensing mode.

17. The control method according to claim 15,
wherein said predetermined image sensing condition is an
20 ON state of storing image sensing conditions.

18. The control method according to claim 15,
wherein said storage step is performed at a time of
shutting down the image sensing apparatus.

25

19. The control method according to claim 15,
wherein said storage step is performed at a time
designated by a user.

5 20. The control method according to claim 15,
wherein all of the image sensing conditions are stored
in said storage step.

10 21. The control method according to claim 15,
wherein at least one of the image sensing conditions is
stored in said storage step.

22. A computer program product comprising a
computer usable medium having computer readable program
15 code means embodied in said medium for a control method
for an image sensing apparatus, said product including:

first computer readable program code means for
determining whether or not a predetermined image sensing
condition was set when the image sensing apparatus was
20 last shut down;

second computer readable program code means for, in
a case where the predetermined image sensing condition
was set, reading the image sensing conditions stored in
memory; and

25 third computer readable program code means for
setting the read image sensing conditions in a case
where the predetermined image sensing condition was set,

or default image sensing conditions in a case where the predetermined image sensing condition was not set, in the image sensing apparatus when turning on the image sensing apparatus.

5

23. The computer program product according to claim 22 further including:

fourth computer readable program code means for determining whether or not a predetermined image sensing
10 condition is set; and

fifth computer readable program code means for storing the image sensing conditions in a case where the predetermined image sensing condition is set.